

DATE PREPARED: 03/18/15

SECTION 1 - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME

HI-FLEX PA-100 PRIMER ADHESIVE

SUPPLIER NAME AND ADDRESS

EMERGENCY TELEPHONE NUMBER:

Lexsuco 2010 Corporation 3275 Orlando Dr.

CANUTEC 613-996-6666 (24 hours every day)

Mississauga, ON L4V 1C5

Regulatory Information Number:

Tel: 905.792.8300 Fax: 905.792.8305

Tel: 1-877-792-8308

Chemical Family: Primer

Product Use: Cleaning and Priming EPDM Single-Ply Roofing Membranes

Restrictions on Use: For industrial use only

SECTION 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 2
Skin Corrosion/Irritation - Category 2
Serious Eye Damage/Eye Irritation - Category 2A
Specific Target Organ Toxicity - Single Exposure - Category 3
Specific Target Organ Toxicity - Repeated Exposure - Category 2

GHS Label Elements







Signal Word

Danger

Hazard Statement(s)

Highly flammable liquid and vapor

Causes skin irritation

Causes serious eye irritation

May cause respiratory irritation.

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

Precautionary Statement(s)

Prevention

Keep container tightly closed

Keep away from heat/sparks/open flame/hot surfaces - No smoking

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Take precautionary measures against static discharge

Use only non-sparking tools

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapours/spray

Response

In case of fire: Use appropriate media to extinguish

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse Call a POISON

CENTER or doctor if you feel unwell Specific treatment (see label)

Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up Keep cool

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
108-88-3	Toluene	60-100
64742-89-8	Heptane	5-10
Trade Secret	Phenolic resin	0.1-1
Trade Secret	Silicon adsorbent mixture	0.1-1
54914-37-3	Isophorondiamine-isobutyraldimine	0.1-1
Trade Secret	Dibutyltin dilaurate	< 0.1
Trade Secret	Isophorone diisocyanate	0.1-1

SECTION 4 - FIRST AID MEASURES

Description of Necessary Measures

If exposed or concerned: Call a POISON CENTER or doctor/physician.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Give artificial respiration if not breathing. Immediately call a POISON CENTER or doctor/physician.

Skin

Remove/Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.

Eyes

Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

If swallowed, do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Most Important Symptoms/Effects Acute

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Causes damage to central nervous system.

Delayed

Prolonged exposure may cause liver, kidney and central nervous system damage.

Note to Physicians

Contains: toluene, heptane.

SECTION 5 - FIRE FIGHTING MEASURES

Extinguishing Media Suitable Extinguishing Media

Dry chemical, foam or carbon dioxide. Water may be ineffective. Use water spray to keep containers cool.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Can burn and explode easily when exposed to open flames or high heat.

Hazardous Combustion Products

Oxides of carbon

Fire Fighting Measures

Wear full protective firefighting gear including self-contained breathing apparatus (SCBA) for protection against possible exposure.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all sources of ignition. Avoid breathing vapors. Ventilate affected area. Absorb with earth, sand or other non-combustible material and transfer to container. Use non-sparking tools. Dike for later disposal.

Environmental Precautions

Avoid release to the environment.

SECTION 7 - HANDLING & STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Keep away from heat/sparks/open flames/hot surfaces. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Use non-sparking tools. Use only outdoors or in a well-ventilated area. Vapors will travel. Prevent vapors from entering buildings through open windows or ventilation systems. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid contact during pregnancy/while nursing. KEEP OUT OF REACH OF CHILDREN.

Conditions for Safe Storage, Including any Incompatibilities Store in a well-ventilated place. Keep container tightly closed Keep cool

Store locked up

Keep away from heat and ignition sources. Keep away from incompatible materials. Do not cut, puncture, or weld on or near this container.

SECTION 8 - EXPOSURE CONTROL & PERSONAL PROTECTION

Component Exposure Limits:

Component Ex						
Toluene	108-88-3					
ACGIH:	20 ppm TWA					
NIOSH:	100 ppm TWA; 375 mg/m3 TWA	150 ppm STEL; 560 mg/m3 STEL				
	500 ppm IDLH	'				
Europe:	50 ppm TWA; 192 mg/m3 TWA	100 ppm STEL; 384 mg/m3 STEL				
	Possibility of significant uptake through	the skin				
OSHA (US):	200 ppm TWA	300 ppm Ceiling				
Mexico:	50 ppm TWA LMPE-PPT; 188 mg/m3	TWA LMPE-PPT				
	Skin - potential for cutaneous absorption					

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment Eye/face protection

Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate work clothing. Wear protective shoes. Recommended material: protective skin cream.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

Appearance	dark liquid	Physical State	liquid
Odor	hydrocarbon	Color	olive,green,dark gray
Odor Threshold	Not available	рН	Not available
Melting Point	-95 °C (-139 °F)	Boiling Point	90 - 111 °C (194-231 °F)
Freezing point	Not available	Evaporation Rate	2.5

Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	230 °C (475 °F)	Flash Point	-7.2 °C (19 °F)
Lower Explosive Limit	1 %	Decomposition	Not available
Upper Explosive Limit	7 %	Vapor Pressure	24.9 mmHg
Vapor Density (air=1)	3.2	Specific Gravity (water=1)	Not available
Water Solubility	Negligible	Partition coefficient: n- octanol/water	Not available
Viscosity	<200 cps	Solubility (Other)	Not available
Density	0.88 (relative)	VOC	727 g/L

Other Information

No information available for the product.

SECTION 10 - STABILITY & REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

Incompatible Materials

Strong oxidizing agents, acids, bases, amines

Hazardous decomposition products

Oxides of carbon

SECTION 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure Inhalation

May cause respiratory irritation. May cause drowsiness or dizziness.

Skin Contact

Causes skin irritation.

Eye Contact

Causes serious eye irritation.

Ingestion

May cause gastrointestinal irritation.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50: The components of this material have been reviewed in various sources and the following selected endpoints are published:

Toluene (108-88-3)

Oral LD50 Rat 2600 mg/kg Dermal LD50 Rabbit 12000 mg/kg Inhalation LC50 Rat 30 - 35 mg/L 4

Heptane (64742-89-8)

Oral LD50 Mouse 5000 mg/kg Dermal LD50 Rabbit 3000 mg/kg

Silicon adsorbent mixture (Trade Secret)

Oral LD50 Rat >32000 mg/kg Dermal LD50 Rabbit >2000 mg/kg

Dibutyltin dilaurate (Trade Secret)

Oral LD50 Rat 45 mg/kg Dermal LD50 Rabbit 630 mg/kg

Isophorone diisocyanate (Trade Secret)

Oral LD50 Rat >20000 mg/kg Dermal LD50 Rabbit >2000 mg/kg Inhalation LC50 Rat 5 mg/L 4 h

Immediate Effects

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to central nervous system.

Delayed Effects

Prolonged exposure may cause liver, kidney and central nervous system damage.

Irritation/Corrosivity Data

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Respiratory Sensitization

No data available.

Dermal Sensitization

No data available.

Component Carcinogenicity

Component Car	emogenicity
Toluene	108-88-3
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

Causes damage to central nervous system.

Specific Target Organ Toxicity - Repeated Exposure

Prolonged exposure may cause liver, kidney and central nervous system damage.

Aspiration hazard

May cause aspiration hazard.

Medical Conditions Aggravated by Exposure

Aspiration into the lungs may cause chemical pneumonitis.

Additional Data

No additional information available.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Avoid release to the environment.

Component Analysis - Aquatic Toxicity

Toluene Toluene	108-88-3
Totache	100-00-3
Fish:	LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L [flow-through] (1 day old); LC50 96 h Pimephales promelas 12.6 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.8 mg/L [semi-static]; LC50 96 h Lepomis macrochirus 11 - 15 mg/L [static]; LC50 96 h Oryzias latipes 54 mg/L [static]; LC50 96 h Poecilia reticulata 28.2 mg/L [semi-static];
	LC50 96 h Poecilia reticulata 50.87 - 70.34 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata >433 mg/L IUCLID; EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L [static] EPA
Invertebrate:	EC50 48 h Daphnia magna 5.46 - 9.83 mg/L [static] EPA; EC50 48 h Daphnia magna 11.5 mg/L IUCLID
Heptane	64742-89-8
Algae:	EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID
Isophorone diisocyanate	Trade Secret
Fish:	LC50 96 h Oncorhynchus mykiss 9.22 mg/L
Invertebrate:	EC50 48 h Daphnia magna 6.14 mg/L IUCLID

Persistence and Degradability

No data available.

Bioaccumulative Potential

No data available.

Mobility

No data available.

Other Toxicity

No information available for the product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14 - TRANSPORT INFORMATION

US DOT Information: Shipping Name: Adhesives

Hazard Class: 3 UN/NA #: UN1133 Packing Group: II

Required Label(s): Red flammable liquid

IATA Information:

Shipping Name: ADHESIVES

Hazard Class: 3 UN#: UN1133 Packing Group: II Required Label(s): 3

TDG Information:

Shipping Name: ADHESIVES

Hazard Class: 3 UN#: UN1133 Packing Group: II Required Label(s):

SECTION 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4),

TSCA 12(b), and/or require an OSHA process safety plan.

1501112(0), 4114	or reduire an extra process surely plan.
Toluene	108-88-3
SARA 313:	1 % de minimis concentration
CERCLA:	1000 lb final RQ; 454 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Toluene	108-88-3
Repro/Dev. Tox	developmental toxicity, initial date 1/1/91
	female reproductive toxicity, initial date 8/7/09

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

100 00 2
108-88-3
1 %
Trade Secret
1 %

Component Analysis - Inventory

Toluene (108-88-3)

	(200 0	,									
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Heptane (64742-89-8)

P	- (- 0, 0,									
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Isophorondiamine-isobutyraldimine (54914-37-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	No	No	Yes	Yes	No

Dibutyltin dilaurate (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Isophorone diisocyanate (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

SECTION 16 - OTHER INFORMATION

HMIS Rating

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Kev / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIstsTM

- ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Reference: The information herein is presented in good faith and believed to be correct as of the date hereof. Information is based upon supplier issued material safety data sheets and may be subject to error. If apprised of changes, updated MSDS will be promptly issued. Users must make their own determination regarding the suitability of the product for their own purposes prior to use.

Prepared By: Lexsuco 2010 Corporation