



LEXCAN MATERIAL SAFETY DATA SHEET

DATE PREPARED: 04/02/15

SECTION 1 - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME

PVC MEMBRANE CLEANER

SUPPLIER NAME AND ADDRESS

*Lexsuco 2010 Corporation
3275 Orlando Dr.
Mississauga, Ontario L4V 1C5
Tel: 905.792.8800 Fax: 905.792.8801*

EMERGENCY TELEPHONE NUMBER:

CANUTEC 613-996-6666 (24 hours every day)

Regulatory Information Number:

Tel: 1-877-792-8308

Chemical Formula:

Mixture

General Use:

Cleaning Solution for Weathered PVC Membranes

SECTION 2 - HAZARDS IDENTIFICATION

HMIS

H	1
F	3
R	0

PPE†

†Sec. 8

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Danger – Highly flammable liquid and vapour

Warning – Causes skin irritation

Warning – Causes serious eye irritation

Danger – May be fatal if swallowed and enters airways

Warning – May cause an allergic skin reaction

Warning – May cause respiratory irritation

Potential Health Effects

Eye: Exposure can cause eye irritation. Symptoms may include stinging, tearing, redness and swelling.

Skin: Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying and cracking, and skin burns. Skin absorption is possible, but harmful effects are not expected from this route of exposure under normal conditions of handling and use.

Swallowing: Single dose oral toxicity is low. Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

Inhalation: Exposure to vapour or mist is possible. Short-term inhalation toxicity is low. Breathing small amounts during normal handling is not likely to cause harmful effects; breathing large amounts may be harmful. Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits.

Symptoms of Exposure: Mouth and throat irritation, gastrointestinal irritation (nausea, vomiting, diarrhea), irritation (nose, throat, respiratory tract), cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), central nervous system (CNS) depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other CNS effects, high blood sugar, coma.

Target Organ Effects: This material (or a component) shortens the time of onset or worsens the liver and kidney damage induced by other chemicals. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate pre-existing disorders of these organs in humans: mild, reversible liver effects, mild, reversible kidney effects.

Developmental Information: This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Cancer Information: No data

Other Health Effects: No data

Primary Route(s) of Entry: Inhalation, Skin absorption, Skin contact, Eye contact

SECTION 3 - INFORMATION ON INGREDIENTS

Hazardous Ingredient Name	CAS #	% wt
Acetone	67-64-1	100%

SECTION 4 - FIRST AID MEASURES

Eyes: If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin: Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing: Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with the head down. Seek medical attention. If possible, do not leave individual unattended.

Inhalation: If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians: This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: -20°C (-4°F)

Flash Point Method: Closed Cup

Autoignition Temperature: 465°C (869°F)

LEL: 2.6%

UEL: 12.8%

Flammability Classification: Flammable Liquid

Extinguishing Media: Alcohol foam, carbon dioxide, dry chemical.

Unusual Fire or

Explosion Hazards: Material is highly volatile and readily gives off vapours which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from the material handling point. Never use welding or cutting torch on or near can (even empty) because product (even just residue) can ignite explosively.

Hazardous Combustion**Products:** Toxic gases or vapours, such as carbon monoxide or carbon dioxide may be released in a fire.**Fire-Fighting Instructions:****Fire-Fighting Equipment:** Water may be ineffective. Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.**SECTION 6 - ACCIDENTAL RELEASE MEASURES****Small Spills:** Absorb liquid on vermiculite, floor absorbent or other absorbent material.**Large Spills:** Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from the area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.**SECTION 7 - HANDLING & STORAGE****Handling Precautions:**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapour, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five-gallon pails and larger metal containers should be grounded and/or bonded when material is transferred. Warning. Sudden release of hot organic chemical vapours or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

SECTION 8 - EXPOSURE CONTROL & PERSONAL PROTECTION**Hazardous Ingredients:**

Ingredient	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH IDLH
	TWA	STEL	TWA	STEL	TWA	STEL	
Acetone	1000 ppm	1000 ppm	500 ppm	750 ppm	250 ppm	None estab.	2500 ppm

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).**Respiratory Protection:** If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.**Eye Protection:** Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.**Skin Protection:** Permeation resistant gloves (that meet ANSI/ISEA 105-2005) recommended. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.**Safety Stations:** Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

Physical State:	Clear, Colourless, Volatile Liquid	Water Solubility:	Complete
Appearance and Odour:	Characteristic Sweetish Odour	Other Solubilities:	Easily Soluble in methanol and diethyl ether.
Odour Threshold :	100 ppm	Boiling Point:	56.1°C (133°F)
Vapour Pressure:	181 mm of Hg (@20°C/68°F)	Freezing/Melting Point:	-95.4°C (-139.6°F)
Vapour Density (Air=1):	2	Viscosity:	N/A
Formula Weight:	58.1 Molecular Weight	Refractive Index:	N/A
Density:	6.590 lbs/gal @ 20°C (68°F)	% Volatile:	100
Specific Gravity (H₂O=1, at 4°C/39°F):	0.79	Evaporation Rate:	11.6 (Butyl Acetate=1)
pH:	7	Flash Point:	-20°C (-4°F)
VOC (gpl):	VOC Exempt	Flash Point Method:	Closed Cup
		Autoignition Temperature:	465°C (869°F)
		LEL:	2.6%
		UEL:	12.8%

SECTION 10 - STABILITY & REACTIVITY

Stability: Stable.

Possibility of Hazardous Reactions: Will not occur.

Chemical Incompatibilities: Avoid contact with acids, strong oxidizing agents.

Conditions to Avoid: Avoid heat, sparks and open flame

Hazardous Decomposition Products: Toxic gases or vapours such as carbon monoxide, carbon dioxide, or oxides of nitrogen may be released in a fire.

SECTION 11 - TOXICOLOGICAL INFORMATION

Toxicity Data: No Data

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: Not Determined

Environmental Fate: Not Determined

Environmental Degradation: Not Determined

Soil Absorption/Mobility: Not Determined

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal: Dispose of in accordance with all local, provincial, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

DOT Transportation Data (49 CFR 172.101):

Shipping Name: Acetone

Shipping Symbols: (3)

Hazard Class: Flammable (3)

ID No.: UN1090

Packing Group: II

Label: 3

Special Provisions (172.102):

IB2, T4, TP1

Packaging Authorizations

a) **Exceptions:** 173.150

b) **Non-bulk Packaging:** 173.202

c) **Bulk Packaging:** 173.242

Quantity Limitations

a) **Passenger, Aircraft, or Railcar:** 5 litres

b) **Cargo Aircraft Only:** 60 litres

Vessel Stowage Requirements

a) **Vessel Stowage:** B

b) **Other:** ---

SECTION 15 - REGULATORY INFORMATION

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification (40 CFR 261): D001

CERCLA Hazardous Substance (40 CFR 302.4): Acetone

CERCLA Reportable Quantity (RQ), 5000 lbs.

SARA 311/312 Codes: Hazard Class – 40 CFR 370.2

Immediate (X) Delayed (X) Fire (X) Reactive ()

Sudden Release of Pressure ()

SARA Toxic Chemical (40 CFR 372.65): Not listed

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed, Threshold Planning Quantity (TPQ)

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed

OSHA Specifically Regulated Substance (29CFR 1910.106)

State Regulations: California Proposition 65: This product contains the following chemical(s) known to the state of California to cause birth defects or other reproductive harm:

New Jersey RTK– Acetone 67-64-1

Pennsylvania RTK – 2-Propanone 67-64-1

SECTION 16 - OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Reference: *The information herein is presented in good faith and believed to be correct as of the date hereof. Information is based upon supplier issued material safety data sheets and may be subject to error. If apprised of changes, updated MSDS will be promptly issued. Users must make their own determination regarding the suitability of the product for their own purposes prior to use.*

Prepared By: Lexsuco 2010 Corporation