

LEXCAN

HI-PRO PVC

Cut Edge Sealant

DESCRIPTION & USE

Lexcan Hi-Pro PVC Cut Edge Sealant is an translucent, polymeric material developed to seal cut edges of PVC membrane. The sealant helps protect the exposed scrim reinforcement from the effects of weather.

TECHNICAL DATA

Physical Properties	
Base:	PVC
Colour:	Translucent
Solids:	18%
Viscosity:	740 cps
Flash Point :	-17°C (1°F)
Net Weight / Gallon:	3.6 kg (7.95 lbs)
Resistance to:	
Ozone	Excellent
UV	Excellent
Water	Excellent
VOC:	750 grams / litre
Packaging:	Twelve 16 oz bottles / carton (5.7 l)
Shelf Life:	1 Year

Coverage Rate

Approximately 70 - 85 m (225 - 275 lin. ft.) per bottle @ 3mm (1/8") diameter bead.

Cautions & Limitations

- Review the applicable Material Safety Data Sheet for complete safety information prior to use.
- Shake well before using. PVC Cut Edge Sealant has a tendency to settle.
- Sealant stored below 15°C (60°F) must be restored to room temperature before using. Temperatures above 32°C (90°F) may affect the shelf life of the Sealant.

APPLICATION INSTRUCTIONS

1. All membrane surfaces receiving Hi-Pro PVC Cut Edge Sealant should be clean, dry, and free from oil, dirt, and all foreign substances.
2. Shake the bottle before using.
3. Apply a 3 mm (1/8") bead of Sealant from the squeeze bottle along the exposed scrim edges of the PVC Membrane. Do not apply Hi-Pro PVC Cut Edge Sealant on vertical surfaces.

lexcan.com

LEXCAN SINGLE PLY ROOFING SYSTEMS

Ontario and Western Canada
1 877 792.8308



Quebec and Eastern Canada
1 800 363.2307